

Countersunk Steel Reduced Head - Semi-Hex Shank - Open Type


Description

Reduced Head Countersunk HEX

Ideal for applications that require an open nut insert and an almost flush head finished with high torque-to-turn ratio.

Specifications


Material Steel
Finish Clear Zinc Plated



Part Number	Thread Size	Grip Range	Hex Hole	Hex Size d2 +0.3	L +0.5	A/F 0.15
INSERTEX M4	M4 x 0.7	0.5-2.5	6.4	7	11	6.3
INSERTEX M5	M5 x 0.8	0.5-3.0	7.3	8	12	7.1
INSERTEX M6	M6 x 1.0	0.5-3.0	9.7	10	14	9.5
INSERTEX M8	M8 x 1.25	0.5-3.0	10.7	12	16	10.5
INSERTEX M10	M10 x 1.50	0.5-3.5	13.0	14.2	18.3	12.8

Thread Size	Pull-Out KN	Push-Out KN	Torque-To-Turn Nm	Maximum Torque
M5 x 0.8	5.8	2.5	7.4	7.8
M6 x 1.0	8.7	2.9	10.3	12.3
M8 x 1.25	9.9	3.7	22.1	31.4

Open End Steel Large Flange - Semi Hex Shank



Part Number	Thread Size	Grip Range (mm)	Hole Size Across Flat +0.1 - 0.00	D	P =0.12	A =0.08	L
INSERTEX M4LF	M4	0.5-2.0	6	9	1.0	5.89	10.0
INSERTEX M5LF	M5	0.5-3.0	7	10	1.0	6.89	13.2
INERTSEX M6LF	M6	0.5-3.0	9	13	1.5	8.89	15.5
INSERTEX M8LF	M8	0.5-3.0	11	16	1.5	10.89	18.0
INSERTEX M10LF	M10	1.0-3.5	13	19	2.0	12.89	21.0

Note: Products in this catalogue are subject to availability



Head Office: Concept Fasteners VIC
 9 Flight Drive, Tullamarine 3043, Victoria
 Tel: (03) 9338 6633 Fax: (03) 9338 6433
 : sales@conceptfasteners.com.au

Head Office: Concept Fasteners NSW
 5 Liverpool St, Ingleburn 2565, NSW
 Tel: (02) 9774 4416
 : salesnsw@conceptfasteners.com.au

Head Office: Concept Fasteners QLD
 Brisbane Branch Coming Soon!
 : qldsales@conceptfasteners.com.au