

## Gas Strut Safety Reminders

### STRUTFORCE GAS STRUTS

Sizes and Pressures available:

6mm stroke 15mm tube	Newtons: 50N - 400N	Overall Size Range: 128mm to 410mm
8mm stroke 18mm tube	Newtons: 50N - 700N	Overall Size Range: 175mm to 750mm
10mm stroke 22mm tube	Newtons: 50N - 1200N	Overall Size Range: 295mm to 975mm
14mm stroke 28mm tube	Newtons: 50N - 2000N	Overall Size Range: 390mm to 910mm
20mm stroke 40mm tube	Newtons: 50N - 3000N	Overall Size Range: 300mm to 1200mm

- Do not attempt to disassemble or drill into the Gas Strut
- Do not lubricate or damage the piston rod as this may damage internal seal
- If not sure about fitting for specific application please contact your local Concept Fasteners Branch for Advice
- Manufacturer Accreditations– Accredited to ISO/TS 16949
- Manufactured under automated processes
- Piston Rod (Shaft)- Salt Spray Test - MIN 144 Hours
- Life Cycle Test - 2 Years / 40,000 Cycles
- High Temperature Test - 80 Deg C
- Low Temperature test - -30 Deg C
- Custom labels upon request
- Manufacturer Approved to ISO14001 and intensive quality control systems in accordance with ISO/TS 16949



**Note: Products in this catalogue are subject to availability**



**Head Office: Concept Fasteners VIC**  
 9 Flight Drive, Tullamarine 3043, Victoria  
 Tel: (03) 9338 6633 Fax: (03) 9338 6433  
 : sales@conceptfasteners.com.au

**Concept Fasteners NSW**  
 5 Liverpool St, Ingleburn 2565, NSW  
 Tel: (02) 9774 4416  
 : salesnsw@conceptfasteners.com.au

**Concept Fasteners QLD**  
 Brisbane Branch Coming Soon!  
 : qldsales@conceptfasteners.com.au